

## Chair 4 stars swivel base with castors

Shell: recyclable polypropylene reinforced with fiberglass.

Upholstered options: polypropylene shell with frontal upholstery, seat cushion only or fully upholstered (seat height + 4 cm)

Covers: fabric, faux-leather or C.O.M. (preferably in solid colour)

Base: die-cast aluminium frame available in powder coated or brushed finish.

Castors: self-braking castors.



Chair	Article	Finish / Upholstery	Powder coated base	Polished brushed (67) base	pcs / dimensions volume / gross weight product net weight
Polypropylene	R0105	Polypropylene			1 pc / 49x58x85,5 cm cm 0,26 m3 / 8,7 Kg 6,5 Kg
Polypropylene with frontal upholstery	R0106	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)			1 pc / 49x58x85,5 cm cm 0,26 m3 / 10 Kg 8 Kg
Polypropylene with seat cushion only	R0107	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)			1 pc / 49x58x85,5 cm cm 0,26 m3 / 9,6 Kg 7,5 Kg
Fully Upholstered	R0113	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)			1 pc / 49x58x85,5 cm cm 0,26 m3 / 10,4 Kg 8,4 Kg


## Fire-retardant version

Fire-retardant version black colour 7F


Fire retardant compounds may cause slightly difference of colours

## Finishes


### Polypropylene



### Metal frame



## Dimensions



## Customer's own material

For customer's own material, the form at the end of the price list shall apply, to be sent to Segis Spa with the Client's signature.

Solid fabric:

for 1 pc seat and back (H. 140 cm ca) 65 cm

for 1 pc seat only (H. 140 cm ca) 40 cm

for 1 pc fully upholstered (H.140 cm ca) 120 cm

## Fire retardant certifications

Art. R0105 meets Class 2 Standards by the Italian Minister of Interior.

## Resistance tests

R0105

EN 16139 :2013 4.1 - General requirements

EN 16139 :2013 4.2.1 - Shear and squeeze points when setting up and folding

EN 16139 :2013 4.2.3 - Shear and squeeze point during use

EN 16139 :2013 4.3.1 - General

EN 16139 :2013 4.3.2 - Swiveling chairs

EN 16139 :2013 4.4 - Rolling resistance of the unloaded chair

EN 16139 :2013 4.5 - Safety of the construction

EN 16139 :2013 5. - Safety, strength and durability requirements

EN 16139 :2013 6. - Test methods

BS EN 1728:2012 6.4 - Seat and back static load test

BS EN 1728:2012 6.5 - Seat front edge static load test

BS EN 1728:2012 6.6 - Vertical static load on back

BS EN 1728:2012 6.15 - Leg forward static load test

BS EN 1728:2012 6.16 - Leg sideways static load test

BS EN 1728:2012 6.17 - Combine seat and back durability test

BS EN 1728:2012 6.18 - Seat front edge durability test

BS EN 1728:2012 6.24 - Seat impact test

BS EN 1728:2012 6.28 - Backward fall test