

Stacking chair 4 legged base.

Shell: recyclable polypropylene reinforced with fiberglass

Polypropylene protective cover under the seat.

Upholstered options: polypropylene shell with frontal upholstery, seat cushion only or fully upholstered (seat height + 4 cm.)

Covers: fabric, faux-leather or C.O.M. (preferably in solid colour)

Frame: steel tube Ø 18 mm available in powder coated or chromed finish.

Glides: thermoplastic material.



	Article	Finish / Upholstery	Powder coated frame	Chromed frame	Galvanic frame 07, 59, 57	pcs / dimensions volume / gross weight product net weight
Chair						
Polypropylene	S0160 S0160 E	Polypropylene Polypropylene for outdoor use				4 pcs / 58,5x71,5x103 cm 0,43 m3 / 26 Kg 5,5 Kg
Polypropylene with frontal upholstery	S0161	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)				2 pcs / 58,5x61,5x93,5 cm 0,34 m3 / 17,9 Kg 7,7 Kg
Polypropylene with seat cushion only	S0162	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)				2 pcs / 58,5x61,5x93,5 cm 0,34 m3 / 15,9 Kg 6,7 Kg
Fully Upholstered	S0163	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)				2 pcs / 58,5x61,5x93,5 cm 0,34 m3 / 18 Kg 8 Kg

Accessories

Kart Universal trolley - art. C0514


Fire-retardant version

Fire-retardant version black colour 7F


Fire retardant compounds may cause slightly difference of colours

Finishes


Polypropylene



Metal frame



Dimensions



Customer's own material

For customer's own material, the form at the end of the price list shall apply, to be sent to Segis Spa with the Client's signature.

Solid fabric:

for 1 pc seat and back (H. 140 cm ca) 65 cm

for 1 pc seat only (H. 140 cm ca) 40 cm

for 1 pc fully upholstered (H.140 cm ca) 120 cm

Fire retardant certifications

Art. S0160 meets Class 2 Standards by the Italian Minister of Interior.

Art. S0161 and Art. S0162 upholstered with Xtreme fabric meet Class 1IM Standards by the Italian Minister of Interior.

Resistance tests

Mod. To-Be S0160

EN 16139:2013 – general requirements of resistance test

EN 1728:2012 – seat and back static load test

EN 1728:2012 – seat and back static vertical load test

EN 1728:2012 – seat and back fatigue test

EN 1728:2012 – seat front edge fatigue test

EN 1728:2012 – front legs static load test

EN 1728:2012 – side legs static load test

EN 1728:2012 – seat impact test

EN 1728:2012 – back impact test

EN 1728:2012 – stability test

ANSI-BIFMA 5.1 -2017/6 – back drop test

ANSI-BIFMA 5.1 -2017/7 – seat drop test

ANSI-BIFMA 5.1 -2017/10 – seat durability test

ANSI-BIFMA 5.1 -2017/11 – stability test

ANSI-BIFMA 5.1 -2017/15 – back durability test / non tilting seat

ANSI-BIFMA 5.1 -2017/17 – front legs static load test

ANSI-BIFMA 5.1 -2017/17 – side legs static load test

ANSI-BIFMA 5.1 -2017/24 – frame fatigue test

Stacking chair 4 legged base with armrests

Shell: recyclable polypropylene reinforced with fiberglass

Polypropylene protective cover under the seat.

Upholstered options: polypropylene shell with frontal upholstery, seat cushion only or fully upholstered (seat height + 4 cm.)

Covers: fabric, faux-leather or C.O.M. (preferably in solid colour)

Frame: steel tube Ø 18 mm available in powder coated or chromed finish

Glides: thermoplastic material.



	Article	Finish / Upholstery	Powder coated frame	Chromed frame	Galvanic frame 07, 59, 57	pcs / dimensions volume / gross weight product net weight
Chair with armrests						
Polypropylene	S0160 B	Polypropylene				4 pcs / 68x71,5x103 cm 0,50 m3 / 35 Kg 7,2 Kg
Polypropylene with frontal upholstery	S0161 B	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)				2 pcs / 68x61,5x93,5 cm 0,45 m3 / 21,5 Kg 9,4 Kg
Polypropylene with seat cushion only	S0162 B	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)				2 pcs / 68x61,5x93,5 cm 0,45 m3 / 19,5 Kg 8,4 Kg
Fully Upholstered	S0163 B	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)				2 pcs / 68x61,5x93,5 cm 0,45 m3 / 20,4 Kg 9,7 Kg

Accessories

Kart Universal trolley - art. C0514


Fire-retardant version

Fire-retardant version black colour 7F


Fire retardant compounds may cause slightly difference of colours

Finishes


Polypropylene



Metal frame



Dimensions



Customer's own material

For customer's own material, the form at the end of the price list shall apply, to be sent to Segis Spa with the Client's signature.

Solid fabric:

for 1 pc seat and back (H. 140 cm ca) 65 cm

for 1 pc seat only (H. 140 cm ca) 40 cm

for 1 pc fully upholstered (H.140 cm ca) 120 cm

Fire retardant certifications

Art. S0160 B meets Class 2 Standards by the Italian Minister of Interior.

Art. S0161B and S0162 B upholstered with Xtreme fabric meet Class 11M Standards by the Italian Minister of Interior.

Resistance tests

Art. S0160B

EN 16139 :2013 4.1 - General requirements

EN 16139 :2013 4.3.1 General

EN 16139 :2013 4.3.3 Non-swiveling chairs

EN 16139 :2013 4.5 Safety of the construction

EN 16139 :2013 5. Safety, strength and durability requirements

EN 16139 :2013 6. - Test methods

BS EN 1728:2012 6.4 - Seat static load and back static load test

BS EN 1728:2012 6.5 - Seat front edge static load test

BS EN 1728:2012 6.6 - Vertical static load test

BS EN 1728:2012 6.10 - Armrest sideways static load test

BS EN 1728:2012 6.11 - Armrest downwards static load test

BS EN 1728:2012 6.13.1 - Seating which may be moved when occupied

BS EN 1728:2012 6.15 - Leg forward static load test

BS EN 1728:2012 6.16 - Leg sideways static load test

BS EN 1728:2012 6.17 - Combine seat and back durability test

BS EN 1728:2012 6.18 - Seat front edge durability test

BS EN 1728:2012 6.20 - Armrest durability test

BS EN 1728:2012 6.24 - Seat impact test

BS EN 1728:2012 6.26 - Arm impact test

BS EN 1728:2012 6.28 - Backward fall test